# VESTAL ASPHALT, INC.

## **Material Safety Data Sheet**

Date Last

Revised 3/2	28/08
-------------	-------

# I. General Information

Chemical Name & Synonyms	Trade Name & Synonyms
Petroleum Hydrocarbons	Asphalt Emulsion HFMS-2
Chemical Family	Formula
Petroleum Hydrocarbons	Asphalt, Water, Surfactant
Proper DOT Shipping Name	DOT Hazard Classification
Asphalt Emulsion	N/A
Manufacturer	Manufacturer's Phone Number
VESTAL ASPHALT, INC.	(607)785-3393
Manufacturer's Address	Chemtrec Phone Number
201 Stage Road Vestal, NY 13850	1-800-424-9300

**II.** Ingredients

Principal Hazardous Component	Percent	Threshold Limit (units)
Petroleum Asphalt	67.0%	N/A
Water	32.5%	N/A
Surfactant	.5%	N/A

III. Physical Data

Boiling Point (°F)	Specific Gravity(H <sub>2</sub> 0 =1)
212 deg. F	<u>0.983 @ 15.6</u> deg. C
Vapor Pressure (mm Hg)	Percent Volatile By Volume (%)
60 mm Hg @ 100 deg. F	32
Vapor Density (Air =1)	Evaporation Rate
N/A	N/A
Solubility in Water	pH
Readily dispersible in water	7-10
Appearance & Odor	
Tan to dark liquid	

IV. Fire & Explosion Hazard Data

Flash Point	Auto Ignition T	Auto Ignition Temperature		
N/A	N/A			
Flammable Limits	LEL	UEL		
N/A	N/A	N/A		
Extinguishing Media	Extinguishing Media			
CO2, Dry Chemical, Foam, Water, Fog				
Special Fire Fighting Procedures				
Do not enter any enclosed space without proper protective equipment. Read entire MSDS.				
Unusual Fire & Explosion Hazards				
Do not weld or drill container. Emptied container still contains material which might ignite with				

Explosive violence if heated.

### V. Health Hazard Data

OSHA Permissible Limits	ACGIH Threshold Limit Value
No standard for asphalt fumes	No standard for asphalt fumes
Carcinogen – NTP Program	Carcinogen – IARC Program
No association has been established	No association has been established
Symptoms of Exposure	
N/A	
Medical Conditions Aggravated by Exposure	
N/A	
Primary Routes of Entry	
N/A	
Emergency First Aid	
N/A	

VI. Reactivity Data

			vi. Reactivity Data
Stability		Unstable	Conditions to Avoid
	X	Stable	N/A
Incompatibi	lity		Materials to Avoid
			May react with strong oxidizing material
Hazardous		May Occur	Conditions to Avoid
Polymeriz	X	Will Not	N/A
ation		Occur	
Hazardous I	Deco	omposition Products	

Normal combustion forms carbon dioxide and may produce oxides of sulfur.

#### **VII. Environmental Protection Procedures**

Spill Response Follow prescribed procedures for reporting and responding to large spills. Clean up small spills with sorbent materials or pumping. Waste Disposal Method Place materials in disposable containers and dispose of in a manner consistent with local and applicable regulations.

> VIII. **Special Protection Information**

Eye Protection	Skin Protection
Use chemical safety glasses	Avoid prolonged skin contact
Respiratory Protection (Specific Type)	Ventilation Recommended
Wear approved respiratory protection	Use in well ventilated area
Other Protection	
As needed	

IX. **Special Precautions**